



High Definition VideoScope Inspection Camera Kits

Narrow diameter cameras with 5.7" High Definition Color LCD* Monitor Deliver high image resolution on large color display where images and videos can be stored on SD memory card (included)

Features:

 Model HDV610 kit - HDV600 VideoScope and 5.5mm diameter camera head with 1m flexible cable

Model HDV620 kit - HDV600 VideoScope and 5.8mm diameter camera head with 1m semi-rigid cable


- 5.7" color LCD* TFT with high definition 640 x 480 VGA pixel resolution
- · Mini, high-resolution water-proof (IP57) camera head
- Rugged oil/chemical resistant and water/drop proof housing (IP67/2m)
- · Non-slip ergonomic handles for ambidextrous use
- SD memory card included to store >15,000 images
- · Video recording (up to 4 hours) with Voice annotation
- AV output for viewing images and video directly on a monitor
- Video and images can be transferred to a PC via the SD card or USB output
- An optional wireless transmitter (HDV-WTX) connects to your camera cable and allows you to transmit video up to 100ft (30m) from the measurement point to your monitor







- A. Camera with 4 built-in bright LED lights illuminate dark areas.
- B. HDV-WTX Optional Wireless Transmitter transmits video to the main display from tight or hard to reach places up to 100ft (30m) away
- C. Optional Articulating (6mm diameter) camera probes adjust up to 240° viewing angle (see below for ordering)



Ordering Information:

HDV610High Definition VideoScope Kit (5.5mm diameter/1m Flexible Cable) HDV620High Definition VideoScope Kit (5.8mm diameter/1m Semi-Rigid Cable)

Video Inspector Monitor (order camera head separately from accessories listed below) HDV600High Definition VideoScope (Monitor and hard carrying case only)

Uptional camera accessories
HDV-TX16mm Articulating VideoScope Camera Head with Macro lens and 1m Semi-Rigid Cable
HDV-WTX16mm Wireless Articulating VideoScope Camera Head w/Macro lens & 1m Semi-Rigid Cable
HDV-TX26mm Articulating VideoScope Camera Head w/Macro lens and 2m Semi-Rigid Cable
HDV-WTX26mm Wireless Articulating VideoScope Camera Head w/Macro lens & 2m Semi-Rigid Cable
HDV-4CAM-1FM4mm VideoScope Camera Head with Macro lens and 1m Flexible Cable
HDV-4CAM-5FM4mm VideoScope Camera Head with Macro lens and 5m Flexible Cable
HDV-5CAM-1FM5.5mm VideoScope Camera Head with Macro lens and 1m Flexible Cable
HDV-5CAM-3F5.5mm VideoScope Camera Head with long depth of field and 3m Flexible Cable
HDV-5CAM-3FM5.5mm VideoScope Camera Head with Macro lens and 3m Flexible Cable
HDV-5CAM-30FM5.5mm VideoScope Camera Head with Macro lens and 30m Flexible Cable
HDV-5CAM-10F5.5mm VideoScope Camera Head with long depth of field and 10m Flexible Cable
HDV-5CAM-1R5.8mm VideoScope Camera Head with long depth of field and 1m Semi-Rigid Cable
HDV-5CAM-1RM5.8mm VideoScope Camera Head with Macro lens and 1m Semi-Rigid Cable
HDV-5CAM-3R5.8mm VideoScope Camera Head with long depth of field & 3m Semi-Rigid Cable
HDV-5CAM-3RM5.8mm VideoScope Camera Head with Macro lens and 3m Semi-Rigid Cable
HDV-25CAM-10G25mm VideoScope Camera Head with long depth of field and 10m Fiberglass Cable
HDV-25CAM-30G25mm VideoScope Camera Head with long depth of field and 30m Fiberglass Cable
HDV-WTXWireless Transmitter
HDV-PCSpare Patch Cable for HDV Series
ADPTR-HDV Replacement AC Adaptor

HDV610 & HDV620 kits include:

5.7" (14.5cm) size;

5.3" (13.5cm) viewable

up to 4 hours AVI video

640 x 480 VGA pixel resolution

(320 x 240 for 4mm camera)

30 fps frame rate (NTSC & PAL)

2GB SD memory card included (supports up to 32GB SD storage)

· VideoScope HDV600, SD memory card, handset with camera probe and 1m cable (Probe accessories: magnet, 45° mirror, and anti-snag tip), 3.7V rechargable Li-Polymer battery, patch cable, Universal AC adapter (110-240V, four plugs), USB and AV cables, and hard carrying case

Applications:

- Industrial Processing & Manufacturing
- · Heavy Equipment
- HVAC/Boilers
- Aerospace

Borescope

Frame Rate

SD Card

Operating

Pixels

*LCD Color TFT Display

- · Government & Security
- Insurance
- · Mining and Aggregate
- · Aviation AOG and FBO
- Power Generation
- Building Inspection & Commissioning
- · PetroChem/Refineries
- Infrastructure



Camera probes with cable length greater than 3m will be coiled on a spool as shown on the left.





BRD10.....Wireless USB Video Receiver